

Tandem Roller Bearings



Dimensiones principales (mm)			Capacidades de carga básicas (KN)		Peso (kg)	especificaciones_antiguas
d	Dimensión	h	dyc_Cr	stc_Cor		
12	42	41.5	70	157	0.32	M2CT1242
32	78	57.5	161	641.25	2.54	M2CT3278
88.9	190.5	107.95	1359.3	5533.75	14.4	M2CT88190Y
88.9	190.5	107.95	1359.3	5533.75	14.4	M2CT89190
145	385	233	4510.3	20956.25	147.7	M2CT145385
431.8	863	449.275	17180	88560		M2CT431863
4	20	32	16.1	41.25	0.053	T3AR420
4	20	32	20.7	43.75	0.061	T3AR420A
4	20	32	17	42	0.053	T3AR420EA
6	45	69	136	259		T3AR645
12	42	62.4	119.6	300	0.41	T3AR1242E
19	49	67	148.35	425	0.5	T3AR1949E
23	85	97	319.7	1545	3.118	T3AR2385
24	68	70	161.345	772.25	1.4	T3AR2468
24	68	70	161.345	772.25	2.38	T3AR2468A1a
24	68	70	161.345	772.25	1.75	T3AR2468A
24	68	70	161.345	772.25	2.31	T3AR2468A1
28	66	82	333.5	825	1.224	T3AR2866
28	90	98	336.145	1411.25	3.48	T3AR2990
30	73	89	197	267	2.05	T3AR3073
32	78	84	290	847	1.93	T3AR3278

Tandem Roller Bearings

33	105	115	416.3	1916.25	5.42	T3AR33105
38	150	163	934.95	4767.5	15.6	T3AR38150
40	110	123	464.6	2265	6.264	T3AR40110
50	160	167	820	3950		T3AR50160
420	900	768	2900	126000		T3AR420900
5	27	52	40.48	104.5	0.155	T4AR527
5	27	52	40.48	104.5	0.142	T4AR527E
5	37	78	120	228		T4AR537
6	45	92	181.7	466.25	0.72	T4AR645E